

GreenSmart Remote Controlled Greywater Diverter

Diverter Kit with Included Components

Model 22RF-L



Model 22RF-R



Each kit includes components pictured



PRODUCT SPECIFICATIONS

BASIC DIVERTER COMPONENTS	
IAPMO Testing Standard	PS-59 2013
File	# 9198
Actuator	
Voltage	12Vdc
Cycle Time	4 sec.
Working Rotation	90Degrees
Enclosure	ABS
Diverter	
Valve 2"	Ball PVC Ball Valve Slip--Sch 40
	NSF/ANSI 61+372 Rated @150 PSI
	NSF 61
Casing Material	PVC
Control Module	
AC/DC Adaptor	UL Class 2 Power Adapter
	UL Listed E149474
Input	120V AC 60Hz 25W
Output	12V DC 1.2A max
DC Plug	52.5 5.5mm
Fail Safe Battery	9V Alkaline Rechargeable
Fail Safe System	9V Trickle Charge
RF System	2--Channel
	433mhz
Diverter w/Actuator Wt.	3lb.10oz.
Length	12.5"
Width	7.5"
Total Height	9.75"
Total Shipping Weight	8.0lb including carton

Hose Adapter (*Hub Connector Not Included*)

Model 22HA



Shown Attached



DIVERTER HOSE ADAPTER	
Width	2" PVC Bushing to 3/4" Dia. Brass Male Hose Thread Adapter (Standard Garden Hose Size)
Length	3.25"
Weight	3.6o
Total Shipping Weight	1lb



2118 Wilshire Blvd., Suite 303, Santa Monica CA 90403
www.greensmartsc.com

For more information visit our web site or contact us at info@greensmartSC.com

